



iPECS NMS Product Brief

iPECS NMS IS A POWERFUL WEB BASED NETWORK MANAGEMENT TOOL DESIGNED FOR THE SMB TO IMPROVE IT STAFF EFFICEINCY, PERMIT RAPID RESPONSE TO SYSTEM ALARMS, AND OPTIMIZE SYSTEM RESOURCES WITH REMOTE ACCESS TO USAGE STATISTICS AND AUTOMATED ALARM NOTIFICATION.

FAULT MANAGEMENT AND REAL-TIME SYSTEM MONITORING

iPECS NMS monitors registered systems in real-time to deliver fault and alarm event statistics. The NMS Server generates automatic e-mail alerts of fault and alarm defined as critical by the system manager. In addition, while on-line, NMS Server can be configured to notify the NMS Web client while the manager works on other PC tasks. Managers can thus identify critical issues with monitored systems implementing corrective measures before the faults become service affecting or even noticed by users.

INVENTORY MANAGEMENT

iPECS NMS monitors and maintains a list of the resources and components for all registered systems. The list includes the call server, each gateway, terminals and even soft-phones as well as software associated with each system and component. Reports in the form of an Excel file can be generated by the system manager for analysis and inventory accounting within the company.

WEB BASED CLIENT ACCESS

iPECS NMS employs a Web based design for access to management tools and reports. Clients require no special software; using their browser, managers have full access to NMS services to monitor and maintain registered systems, components and applications from anywhere there is IP access.

TRAFFIC STATISTICS

Understanding system resource usage is an effective starting point in managing a communication system. iPECS NMS monitors registered systems to deliver detailed traffic statistics covering use of the various components and resources of the system. Managers can easily analyze the traffic data to determine under and over usage of resources as well as useage trend and adjust system configurations to address any issues. In addition, iPECS NMS provides detailed and summary data for call accounting and cost allocation..

REMOTE MAINTENANCE

Periodically, LGN releases enhancements to iPECS LIK software that are specifically designed to permit direct upload directly over the network. While simple, the process can be tedious and time consuming. With iPECS NMS the repetitive process is reduced to just a few clicks of your mouse assuring accurate efficient and complete upgrades to multiple iPECS systems and components.

EASY INSTALLATION & OPERATION

The iPECS NMS application is designed to easily install in a Windows environment. Following the straight forward install shield instructions, the system manager can quickly complete installation. An intuitive GUI permits the manager to register up to 500 iPECS systems to a single iPECS NMS Server. Registering the monitored systems are also managed by easy to use GUI and up to recommended maximum capacity of 500 systems. System managers can access the monitoring system whenever they want to access and wherever they are. Just by opening Internet Explorer on any networked PC, system managers can take full control of monitored systems.



- REAL TIME MONITORING**
 - Device type based status display | Sub grouped as CO, Station & Others
 - Resource based status display | CO resource, Station resource
 - Device connection status | Disconnected, Registering, Active | T-Net, Downloading, Out of SVC, N/A
 - Channel status for selected device | In use, DND, Idle, Forward | Pre selected message, DECT base connection | Out of SVC, Lock up, T-NET
 - Device information | Device name, number, type, F/W version | CPU, number of channel etc.
 - Device network information | IP, MAC, NAPT IP, ARP on/off | Signal type, Zone number, T-Net etc.
- FAULT MANAGEMENT**
 - Automatic notification | email, audible, visual
 - Notice event type management | None, problematic vs. Device failure, Alarm | Critical, Major, Minor
 - 10,000 event log store
 - Log information field | Fault type, Level, Event code | Event description, NMS system time | System name, Location
 - Event search options | by status, event type, event level | by event code, location, log time
- SYSTEM INFORMATION MANAGEMENT**
 - 4 directory levels & 100 system groups
 - General system registration information | System name, type, IP, S/W version | Channel capacity consumption | IP range, Codec type, Diffserv code etc.
 - Attendant number, type, station number ■ CO group number, CO line number
 - Station group number, type, pick up & station number
 - Per system group device inventory information | Group name, number of system | Maximum channel capacity | Registered number of channels | Total number & type of registered devices
 - Per system inventory information | System name, IP, S/W version | Maximum channel capacity | Registered number of channels | Number & type of registered devices
- SYSTEM CALL & TRAFFIC STATISTICS**
 - Filtered by attendant call, completed call, CO group call, VM usage | period of today, yesterday, last 1 week, last 4 weeks | display by daily, hourly
 - Attendant call filtering options | held call, duration, answer delay | total call, abandoned call
 - Total number of completed calls ■ CO group call options | All CO busy count | Incoming/outgoing seizure, group overflow
 - Voice mail access requested & denied
- SMDR STATISTICS**
 - One click SMDR file download ■ SMDR table and graphical display
 - Max. SMDR log size | MFIM50/100 - 5,000 | MFIM300 - 10,000 | MFIM600 - 15,000
 - Log analysis fields | Station, CO number, time, duration | Dialed number, ring time | Normal calls, abandoned calls etc.
- DECT STATISTICS**
 - DECT base and handset log information
 - General information | Total number of handset | Number of dropped calls | Number of no response calls | Number of WTIM call overflow
 - WTIM related information | Traffic density | Call cut description | RF usage statistics per each cell | Handover failure count & rate
- NETWORK TRAFFIC STATISTICS**
 - General Ping & Trace-route | From NMS server to destination IP ■ iPECS Ping | From MFIM to system device
 - SNMP device data traffic monitoring | Incoming/outgoing packets | SNMP v.1/2 devices
 - iPECS device data traffic monitoring | iPECS gateway | All packets or RTP only
- MULTISITE FIRMWARE UPGRADE**
 - Sequential device F/W upgrade
 - Upgradable devices | All MFIM, Gateways, IP phones
 - Scheduled upgrade ■ Upgrade status and result display
- SYSTEM DB BACK UP**
 - Multi system DB download and upload
 - System DB type | LCR table, System speed dial, Station speed dial | Networking data, Station group data, System data, Flexible numbering plan | Station flexible buttons, RSGM table, Toll table, MSN table | Flexible DID table, Password table, Mobile extension table | ICLID table & registered device table
 - Scheduled DB back up ■ Upload status and result display
- VOICE PROMPT & SYSTEM GREETING UPLOAD**
 - Multi system prompt & greeting management ■ System voice prompt | Total system prompt | Individual .wav file
 - Multi language system greeting | Total system greeting | Individual .wav file | Upload status and result display

Server requirements

| | |
|------------------------------------|--|
| Less than 20 systems registration | Intel Core 2 Duo 2.33 GHz or higher & 2 GB RAM or higher Minimum 4 GB of free disk space |
| Less than 200 systems registration | Intel Dual-Core Zeon 2.4GHz or higher & 2GB RAM or higher Minimum 20GB of free disk space |
| Less than 500 systems registration | Intel Quad-Core Zeon 2.66GHz or higher & 2GB RAM or higher Minimum 50GB of free disk space |
| Server operating system | Microsoft XP Professional or Windows Server 2003 32bit version with NTFS |
| iPECS system device requirements | MFIM firmware version 5.0 or higher (MFIM50/100/300/600) Phase 4 gateways and LIP-7000 IP phones with P5 firmware for full features |